



OHAUS T31 PLASTIC INDICATOR

FOR DRY APPLICATIONS

A LOW COST INDICATOR SUITABLE FOR CONNECTING TO SMALL & LARGE BASES IN PRODUCTION, PACKING, SHIPPING & GOODS-IN AREAS.

OHAUS T31 XW INDICATOR

FOR WET ENVIRONMENTS

WITH IT'S 304 STAINLESS STEEL IP66 ENCLOSURE THIS INDICATOR IS IDEAL FOR ALL FOOD PROCESSING & PACKING OPERATIONS WHICH REQUIRE A SIMPLE TO USE BUT ROBUST UNIT.

**ALSO AVAILABLE
WITH INTERNAL RECHARGEABLE SEALED BATTERY**



DA MODEL 3590 MULTI-FUNCTION INDICATOR

24 KEY ALPHANUMERIC PROGRAMABLE KEYBOARD

IP68 PROTECTION FOR DUST & HUMIDITY

**IDEAL FOR TOTALISATION, FORMULATION,
COUNTING, LABELING, ETC.**

Options:

BUILT IN RECHARGEABLE BATTERY, ETHERNET & WI-FI INTERFACE

UWE W22 INDICATOR WITH INTEGRATED PRINTER

RS232 OUTPUT FOR CONNECTION TO A COMPUTER
OR EXTERNAL PRINTER

ALPHANUMERIC LOT OR SERIAL No ENTRY
PRINTS ,DATE & TIME, & TOTALISES



UWE ATM INDICATOR

CLASS 3 TRADE APPROVED ,ABS CASE, WITH 51mm LCD
DISPLAY

**MAINS OR RECHARGEABLE BATTERY OPTIONS
WALL OR PILLER MOUNTING AVAILABLE**



CNCELL PA8101S INDICATOR

**IP66 RATED STAINLESS STEEL CASE,
WALL BRACKET INCLUDED**

6 DIGIT 20mm RED LED DISPLAY

**SELECTABLE WEIGHING UNITS, PARTS COUNTING, &
ANIMAL WEIGHING MODE
MAINS ONLY**



GSE MODEL662 INTELLEAGENT INDICATOR

**STAINLESS STEEL IP65 CASE,
8 X 40 CHARACTER LCD DISPLAY
8 SCALE INPUT & 32 I/O PORTS
4 SERIAL PORTS**

**THE IDEAL UNIT TO USE WITH A SOFTWARE PACKAGE
THAT CAN BE WRITTEN TO SUIT YOUR NEEDS.**